



Vitasalus, Inc.
"We bring wellness to life!"™

Standard Features

- Powder coated steel frame
- Inlet solenoid valve
- 20" prefilter
- Prefilter pressure gauge
- Multistage centrifugal pump
- Low-pressure protection with microprocessor auto reset
- 2 ½" liquid filled pump pressure gauge
- Stainless steel pressure vessel(s)
- Product flow meter
- Reject flow meter
- Concentrate needle valve
- Non metallic recycle needle valve
- On / off toggle switch
- Feed water and product water TDS monitor



Applications

- Whole house
- Boiler feed water
- Humidifiers
- Greenhouses
- Process Water
- Electronics

Model (RO Master 2200)

Specifications

| | |
|----------------------------|------------------|
| Membrane Size | 4" x 40" |
| Average membrane rejection | 98 % |
| Feed Water Connection | 3/4" NPTF |
| Prefilter | 20" |
| Product Water Connection | 5/8" tubing OD |
| Reject Water Connection | 5/8" tubing OD |
| Feed Water Pressure | (minimum) 10 psi |
| Electrical Requirement | 120 VAC 60 Hz |

Model (RO Master 2200)

| | |
|--|--------------|
| Maximum Productivity (gallons per day) | 2200 |
| Recovery (user adjustable) | 15 - 75 % |
| Number Of Membranes | 1 |
| Feed Water Required (maximum) | 10gpm |
| Drain Required (maximum) | 10gpm |
| Motor Horse Power | 3/4 |
| Electrical Requirement | 15 amps |
| Dimensions W x D x H | 20 x 20 x 50 |
| Shipping Weight (estimated lbs) | 120 |